

AUCAN'S DIESEL GENERATOR SERIES OVERVIEW



New Diesel						
	Diesel Generator Silent Type					
Model	WD2500E	WD3500SE	WD6500SQ	WD7500SQ	WD8500SQ	WD10000SQ
Type	Revolving Magnetic Field,Single Phase,3 wires ,Brushless					
Voltage Regulate	AVR					
AC Frequency(Hz)	50/60					
AC Output Voltage(V)	110,115,120 / 220,230,240					
Cont.AC Output(W)	2200	3200	5500	6500	7500	9000
Max.AC Output(W)	2500	3500	6500	7500	8500	10000
DC Output(V/A)	12V /8.3A					
Engine Model	WD170F	WD178F	WD186F	WD188F	WD192F	WD195F
Type	Forced Air Cooled, Single/Double Cylinder, 4 Stroke, OHV					
Starting System	Recoil/Electric/Remote					
Fuel Tank Capacity(L)	15	16	16	16	16	18
Packing dimensions(mm)	690*470*562	940*560*760	940*560*760	940*560*760	940*560*760	980*580*780
Net Weight(kg/lbs)	88	150	155	160	170	180
Per 20" GP CNT	108	72	72	72	72	72
Per 40" GP CNT	220	144	144	144	144	144
Certificates	EPA/CARB/CE/EU5					

New Design						
	Super Quite Type					
Model	WD12000SQ	WD13000SQ	WD15000SQ	WD16000SQ	WD18000SQ	WD23000SQ
Type	Revolving Magnetic Field,Single Phase,3 wires ,Brushless					
Voltage Regulate	AVR					
AC Frequency(Hz)	50/60					
AC Output Voltage(V)	110,115,120 / 220,230,240					
Cont.AC Output(W)	10000	12000	13000	14000	16000	19000
Max.AC Output(W)	12000	13000	15000	16000	18000	23000
DC Output(V/A)	12V /8.3A					
Engine Model	WD1100F	WD1102F	WD1105F	WD292F	WD295F	WD298F
Type	Forced Air Cooled, Single/Double Cylinder, 4 Stroke, OHV					
Starting System	Recoil/Electric/Remote					
Fuel Tank Capacity(L)	25	25	25	30	30	30
Packing dimensions(mm)	980*760*800	980*760*800	1000*760*800	1250*760*890	1330*820*940	1360*820*940
Net Weight(kg/lbs)	210	220	230	310	350	350
Per 20" GP CNT	34	34	30	24	20	20
Per 40" GP CNT	68	68	60	48	40	40
Certificates	EPA/CARB/CE/EU5					