

AUCAN'S GASOLINE GENERATOR SERIES OVERVIEW



New Gasoline						
	Gasoline Generator					
Model	WG2500X	WG3500X	WG6500PE	WG7500PE	WG8500PE	WG10000PE
Type	Revolving Magnetic Field,Single Phase,3 wires ,Brushless					
Voltage Regulate	AVR					
AC Frequency(Hz)	50/60					
AC Output Voltage(V)	110,115,120 / 220,230,240					
Cont.AC Output(W)	2200	3000	5500	6500	7500	8500
Max.AC Output(W)	2500	3500	6500	7500	8500	10000
DC Output(V/A)	12V /8.3A					
Engine Model	WG168F	WG170F	WG188F	WG190F	WG192F	WG192F
Type	Forced Air/Water Cooled, Single Cylinder, 4 Stroke, OHV					
Starting System	Recoil/Electric/Remote					
Fuel Tank Capacity(L)	15	15	25	25	25	25
Packing dimensions(mm)	610*440*440	610*440*440	690*520*570	690*520*570	690*520*570	760*650*670
Net Weight(kg/lbs)	42	46	80	90	90	100
Per 20" GP CNT	236	236	140	140	140	100
Per 40" GP CNT	590	590	292	292	292	200
Certificates	EPA/CARB/CE/EU5					

New Design						
	Gasoline Generator					
Model	WG12000PE	WG13000PE	WG15000PE	WG18000PE	WG20000PE	WG25000PE
Type	Revolving Magnetic Field,Single Phase,3 wires ,Brushless					
Voltage Regulate	AVR					
AC Frequency(Hz)	50/60					
AC Output Voltage(V)	110,115,120 / 220,230,240					
Cont.AC Output(W)	9000	10000	12000	15000	18000	22000
Max.AC Output(W)	12000	13000	15000	18000	20000	25000
DC Output(V/A)	12V /8.3A					
Engine Model	WG194F	WG194F	WG2V88	WG2V90	WG465F	WG485F
Type	Forced Air/Water Cooled, Single Cylinder, 4 Stroke, OHV					
Starting System	Recoil/Electric/Remote					
Fuel Tank Capacity(L)	25	25	30	30	30	30
Packing dimensions(mm)	760*650*670	760*650*670	1050*630*700	1050*630*700	1150*650*720	1250*650*720
Net Weight(kg/lbs)	110	110	220	220	260	260
Per 20" GP CNT	100	100	40	40	35	32
Per 40" GP CNT	200	200	80	80	70	64
Certificates	EPA/CARB/CE/EU5					